

RSL-382s – Desk Top 1-side/2-side Laminator

Specifications			
Dimensions	H – 470mm	W – 640mm	D – 550mm
Weight	40kg		
Electrical requirements	1200W, 240V, single phase, 13 amps		
Film gauge	25 – 75 micron		
Maximum recommended stock	250gsm		
Minimum recommended stock	200gsm (Single sided) 80gsm (Two sided)		
Maximum sheet size	380mm width x any length		
Minimum sheet size	Any width x 65mm length		
Speed	Up to 4.5m per minute		
Core size	25mm (& 57mm with adapters)		
Heating	Heated Rollers		
Warm up time	10 minutes approx.		
Temperature range	0 – 150° C		
Key Features:			
<ul style="list-style-type: none"> Memory store for frequently used temperature and speed settings. 		<ul style="list-style-type: none"> A manually operated cross cutter to remove a web of double-sided lamination. 	
<ul style="list-style-type: none"> Decurl system to assist giving a flat sheet when laminating one side only. 		<ul style="list-style-type: none"> A take up device to remove the release liner allows the use of cold films. 	

D & K Europe Ltd
 38-39 Crossgate Road, Park Farm Redditch, B98 7SN
 Tel: 01527 520073 Email: uksales@dkeurope.co.uk

