



D&K International

Technical Data Sheet

Product: 2 mil (1/1) Polyester Gloss Packaging Film

Product Code: PET1/1AC

Product Description:

A 2 mil polyester gloss laminating film featuring a thermally-activated adhesive resin. This film is ideal for use in FlexPack applications.

Performance Characteristics:

Characteristics	Target
Total Thickness	2.0 mils
Base Film Type	Polyester (PET)
Base Film Thickness	1.0 mils
Base Film Finish	Gloss (Clear)
Adhesive Thickness	1 mil
Adhesive Type	FlexPack Adhesive
pH	7 (Neutral)
Core Size	3"
Adhesive Activation Temperature	230° - 260° F* Note: Actual running temperature will vary
Bond Type	Permanent

Test Methods

D&K test methods have been internally developed for D&K products and are based upon ASTM and PSTC standardized tests.

Recommended Shelf Life

The recommended shelf life for this product is 12 months from the date of shipment, assuming reasonable storage conditions. It is recommended that the product be consumed within the suggested shelf life.

The above information is presented for reference and illustration of general product characteristics only, and does not reflect the total product offering. The information is provided as a guide and does not constitute a representation or warranty, expressed or implied, relating to the suitability or fitness for a particular application or otherwise create guarantees of product performance. In all cases, customers should independently determine the suitability of D&K products for their specific application before use.