



D&K Group



Technical Data Sheet

Product: Polyester Standard Diamond Hard Velvet Matte Packaging Film

Product Code: PETSTDAMQ

Product Description:

A polyester laminating film with D&K's proprietary Diamond Hard Velvet Matte Finish. This film is ideal for use in FlexPack applications.

Performance Characteristics:

Characteristics	Target
Total Thickness	1.5 mil
Base Film Type	Polyester (PET)
Base Film Thickness	.6 mils
Base Film Finish	Diamond Hard Velvet Matte
Adhesive Thickness	.8 - .9 mils
Adhesive Type	FlexPack Adhesive
Adhesive Activation Temp	230° - 260° F* Note: Actual running temperature will vary
Sutherland RubTest	No Scuffing or changes in Gloss
Tape Adhesion (3M 810)	Excellent
Ball Point Pen Receptivity	Excellent
Fingernail Scuff Resistance	Excellent

Test Methods

D&K test methods have been internally developed for D&K products and are based upon ASTM and PSTC standardized tests.

Recommended Shelf Life

The recommended shelf life for this product is 12 months from the date of shipment, assuming reasonable storage conditions. It is recommended that the product be consumed within the suggested shelf life.

The above information is presented for reference and illustration of general product characteristics only, and does not reflect the total product offering. The information is provided as a guide and does not constitute a representation or warranty, expressed or implied, relating to the suitability or fitness for a particular application or otherwise create guarantees of product performance. In all cases, customers should independently determine the suitability of D&K products for their specific application before use. No employee or representative of D&K is authorized to offer any claims or warranties in addition or counter to this statement.